

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Mixture
Product name	: Chanel No 5 Type #EU35658F
UFI	: GER5-Y3TT-8001-5UXE
Product code	: EU35658F
Type of product	: Perfumes, fragrances
Product group	: Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category	: Professional use, Industrial use
Industrial/Professional use spec	: Industrial For professional use only
Use of the substance/mixture	: Perfumes, fragrances
Function or use category	: Odour agents

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

FRENCH COLOR & FRAGRANCE International GmbH GmbH
Mittlerer Weg 35
DE- 79424 Auggen
Germany
T 49-7631-931-8900
SDS@frenchcolor.com - www.frenchcolor.com

1.4. Emergency telephone number

Emergency number : 1-800-255-3924; +01-813-248-0585; China: +400-120-0751; Mexico: +01-800-099-0731;
Brazil: +0-800-591-6042; India: +000-800-100-4086

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (oral), Category 4	H302
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Skin sensitisation, Category 1	H317
Carcinogenicity, Category 2	H351
Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411
Full text of H- and EUH-statements: see section 16	

Adverse physicochemical, human health and environmental effects

Suspected of causing cancer. Harmful if swallowed. Causes skin irritation. Causes serious eye irritation. Toxic to aquatic life with long lasting effects. May cause an allergic skin reaction.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Chanel No 5 Type #EU35658F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

	GHS07	GHS08	GHS09
Signal word (CLP)	: Warning		
Contains	: Benzyl benzoate, Amyl cinnamic aldehyde, Linalool, Musk ketone, Heliotropine, COUMARIN, Hydroxy, Citronellol Pure, Linalyl acetate, Geraniol, Nerol, d-Limonene, Eugenol, Cinnamic alcohol, Timberol, Methyl salicylate		
Hazard statements (CLP)	: H302 - Harmful if swallowed. H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation. H351 - Suspected of causing cancer. H411 - Toxic to aquatic life with long lasting effects.		
Precautionary statements (CLP)	: P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P264 - Wash hands, forearms and face thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P272 - Contaminated work clothing should not be allowed out of the workplace. P308+P313 - IF exposed or concerned: Get medical advice/attention.		
Extra phrases	: For professional users only.		

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Benzyl benzoate	CAS-No.: 120-51-4 EC-No.: 204-402-9 EC Index-No.: 607-085-00-9 REACH-no: 01-2119976371-33	23.925 – 47.85	Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Amyl cinnamic aldehyde	CAS-No.: 122-40-7 EC-No.: 204-541-5;453-530-3	3.9 – 7.8	Skin Sens. 1B, H317 Aquatic Chronic 2, H411
Benzyl acetate substance with national workplace exposure limit(s) (BE, DK, ES, IE, LT, LV, PT, RO)	CAS-No.: 140-11-4 EC-No.: 205-399-7 REACH-no: 01-2119638272-42	3 – 6	Aquatic Chronic 3, H412
Methyl ionone (mixture of isomers)	CAS-No.: 1335-46-2 EC-No.: 215-635-0	2.7 – 5.4	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 2, H411
Linalool	CAS-No.: 78-70-6 EC-No.: 201-134-4 EC Index-No.: 603-235-00-2 REACH-no: 01-2119474016-42	2.5 – 5	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317

Chanel No 5 Type #EU35658F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Musk ketone	CAS-No.: 81-14-1 EC-No.: 201-328-9 EC Index-No.: 609-069-00-7	2.4 – 4.8	Carc. 2, H351 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Heliotropine	CAS-No.: 120-57-0 EC-No.: 204-409-7 REACH-no: 01-2119983608-21	1.45 – 2.9	Skin Sens. 1B, H317
COUMARIN	CAS-No.: 91-64-5 EC-No.: 202-086-7 REACH-no: 01-2119943756-26	1.4 – 2.8	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Hexamethylindanopyran	CAS-No.: 1222-05-5 EC-No.: 214-946-9 EC Index-No.: 603-212-00-7 REACH-no: 01-2119488227-29	0.75 – 1.5	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Hydroxy	CAS-No.: 107-75-5 EC-No.: 203-518-7 REACH-no: 01-2119973482-31	0.74822 – 1.49644	Eye Irrit. 2, H319 Skin Sens. 1B, H317
Citronellol Pure	CAS-No.: 106-22-9 EC-No.: 203-375-0 REACH-no: 01-2119453995-23	0.612 – 1.24	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317
alpha-Ionone	CAS-No.: 127-41-3 EC-No.: 204-841-6 REACH-no: 01-2119965149-27	0.6 – 1.2	Aquatic Chronic 3, H412
Vanillin	CAS-No.: 121-33-5 EC-No.: 204-465-2 REACH-no: 01-2119516040-60	0.55 – 1.1	Eye Irrit. 2, H319
Linalyl acetate	CAS-No.: 115-95-7 EC-No.: 204-116-4 REACH-no: 01-2119454789-19	0.5 – 1	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
Amyl salicylate	CAS-No.: 2050-08-0 EC-No.: 218-080-2 REACH-no: 01-2119969444-27	0.45 – 0.9	Acute Tox. 4 (Oral), H302 Aquatic Chronic 1, H410
d-Limonene substance with national workplace exposure limit(s) (DE, ES, FI, SI, NO, CH)	CAS-No.: 5989-27-5 EC-No.: 227-813-5 EC Index-No.: 601-029-00-7;601-096-00-2 REACH-no: 01-2119493353-35	0.4 – 0.8	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1B, H317 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 3, H412
Eugenol	CAS-No.: 97-53-0 EC-No.: 202-589-1 REACH-no: 01-2119971802-33	0.4 – 0.8	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 Skin Sens. 1B, H317

Chanel No 5 Type #EU35658F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Cinnamic alcohol	CAS-No.: 104-54-1 EC-No.: 203-212-3 REACH-no: 01-2119934496-29	0.375 – 0.75	Acute Tox. 4 (Oral), H302 Skin Sens. 1B, H317
Geraniol	CAS-No.: 106-24-1 EC-No.: 203-377-1 EC Index-No.: 603-241-00-5 REACH-no: 01-2119552430-49	0.2 – 0.56	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317
Timberol	CAS-No.: 70788-30-6 EC-No.: 274-892-7	0.25 – 0.5	Skin Sens. 1B, H317
Carbitol substance with national workplace exposure limit(s) (AT, DE, EE, SE, SI, CH)	CAS-No.: 111-90-0 EC-No.: 203-919-7 REACH-no: 01-2119475105-42	0.21699 – 0.43398	Not classified
Nerol	CAS-No.: 106-25-2 EC-No.: 203-378-7	0.12 – 0.4	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
Camphene	CAS-No.: 79-92-5 EC-No.: 201-234-8	0.2 – 0.4	Flam. Sol. 2, H228 Eye Irrit. 2, H319 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
para-Cresyl methyl ether	CAS-No.: 104-93-8 EC-No.: 203-253-7	0.175 – 0.35	Acute Tox. 4 (Oral), H302 Repr. 2, H361 Skin Irrit. 2, H315
Cedarwood oil, Texas	CAS-No.: 68990-83-0 EC-No.: 294-461-7	0.125 – 0.25	Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Diphenyl oxide substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH); substance with a Community workplace exposure limit	CAS-No.: 101-84-8 EC-No.: 202-981-2 REACH-no: 01-2119472545-33	0.05 – 0.1	Eye Irrit. 2, H319 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Benzyl alcohol substance with national workplace exposure limit(s) (BG, CZ, DE, FI, LT, LV, PL, SI, CH)	CAS-No.: 100-51-6 EC-No.: 202-859-9 EC Index-No.: 603-057-00-5 REACH-no: 01-2119492630-38	0.05 – 0.1	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319
Methyl salicylate	CAS-No.: 119-36-8 EC-No.: 204-317-7 EC Index-No.: 607-749-00-8	0.05 – 0.1	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318 Skin Sens. 1B, H317 Repr. 2, H361d Aquatic Chronic 3, H412
Benzaldehyde substance with national workplace exposure limit(s) (BG, FI, HU, LT, LV, PL)	CAS-No.: 100-52-7 EC-No.: 202-860-4 EC Index-No.: 605-012-00-5 REACH-no: 01-2119455540-44	0.05 – 0.1	Acute Tox. 4 (Oral), H302

Chanel No 5 Type #EU35658F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Isoamyl acetate substance with national workplace exposure limit(s) (AT, BE, BG, CY, DE, DK, EE, ES, FI, FR, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, TR); substance with a Community workplace exposure limit	CAS-No.: 123-92-2 EC-No.: 204-662-3 EC Index-No.: 607-130-00-2 REACH-no: 01-2119548408-32	0 – 0.05	Flam. Liq. 3, H226
Citral substance with national workplace exposure limit(s) (BE, ES, IE, PL, PT)	CAS-No.: 5392-40-5 EC-No.: 226-394-6 EC Index-No.: 605-019-00-3 REACH-no: 01-2119462829-23	0.004 – 0.024	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention. Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Toxic fumes may be released.
--	--------------------------------

5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.
----------------------	--

Chanel No 5 Type #EU35658F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.
Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.
Storage temperature : 25 °C
Storage area : Store in a well-ventilated place. Store away from heat.
Special rules on packaging : Store in a closed container.
Packaging materials : Do not store in corrodable metal.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Benzyl acetate (140-11-4)	
Belgium - Occupational Exposure Limits	
OEL TWA	62 mg/m ³
OEL TWA [ppm]	10 ppm
Denmark - Occupational Exposure Limits	
OEL TWA [1]	61 mg/m ³
OEL TWA [2]	10 ppm
Ireland - Occupational Exposure Limits	
OEL TWA [2]	10 ppm
OEL STEL [ppm]	30 ppm (calculated)

Chanel No 5 Type #EU35658F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Benzyl acetate (140-11-4)	
Latvia - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	5 mg/m ³
Portugal - Occupational Exposure Limits	
OEL TWA [ppm]	10 ppm
OEL chemical category	A4 - Not Classifiable as a Human Carcinogen
Romania - Occupational Exposure Limits	
OEL TWA	50 mg/m ³
OEL TWA [ppm]	8 ppm
OEL STEL	80 mg/m ³
OEL STEL [ppm]	13 ppm
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA) [1]	62 mg/m ³
VLA-ED (OEL TWA) [2]	10 ppm
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	10 ppm
ACGIH chemical category	Not Classifiable as a Human Carcinogen
Musk ketone (81-14-1)	
Austria - Occupational Exposure Limits	
OEL chemical category	Group B Carcinogen
Citral (5392-40-5)	
Belgium - Occupational Exposure Limits	
OEL TWA	32 mg/m ³ (vapor and aerosol)
OEL TWA [ppm]	5 ppm (vapor and aerosol)
OEL chemical category	Skin
Ireland - Occupational Exposure Limits	
OEL TWA [2]	5 ppm
OEL STEL [ppm]	15 ppm (calculated)
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	27 mg/m ³
NDSch (OEL STEL)	54 mg/m ³
Portugal - Occupational Exposure Limits	
OEL TWA [ppm]	5 ppm
OEL chemical category	Sensitizer, A4 - Not Classifiable as a Human Carcinogen, skin - potential for cutaneous exposure
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA) [2]	5 ppm (inhalable fraction and vapor)
OEL chemical category	Sensitizer, skin - potential for cutaneous absorption

Chanel No 5 Type #EU35658F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Citral (5392-40-5)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	5 ppm (inhalable fraction and vapor)
ACGIH chemical category	Not Classifiable as a Human Carcinogen, Skin - potential significant contribution to overall exposure by the cutaneous route, dermal sensitizer
d-Limonene (5989-27-5)	
Finland - Occupational Exposure Limits	
HTP (OEL TWA) [1]	140 mg/m ³
HTP (OEL TWA) [2]	25 ppm
HTP (OEL STEL)	280 mg/m ³
HTP (OEL STEL) [ppm]	50 ppm
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA) [1]	28 mg/m ³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
AGW (OEL TWA) [2]	5 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Chemical category	Skin notation, Skin sensitization
Slovenia - Occupational Exposure Limits	
OEL TWA	28 mg/m ³
OEL TWA [ppm]	5 ppm
OEL STEL	112 mg/m ³
OEL STEL [ppm]	20 ppm
OEL chemical category	Potential for cutaneous absorption
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA) [1]	168 mg/m ³
VLA-ED (OEL TWA) [2]	30 ppm
OEL chemical category	Sensitizer, skin - potential for cutaneous absorption
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA) [1]	140 mg/m ³
Grenseverdi (OEL TWA) [2]	25 ppm
Korttidsverdi (OEL STEL)	175 mg/m ³ (value calculated)
Korttidsverdi (OEL STEL) [ppm]	37.5 ppm (value calculated)
OEL chemical category	Allergenic substance
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA) [1]	40 mg/m ³
MAK (OEL TWA) [2]	7 ppm
KZGW (OEL STEL)	80 mg/m ³
KZGW (OEL STEL) [ppm]	14 ppm
OEL chemical category	Sensitizer

Chanel No 5 Type #EU35658F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Carbitol (111-90-0)	
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	35 mg/m ³
MAK (OEL TWA) [ppm]	6 ppm
MAK (OEL STEL)	140 mg/m ³
MAK (OEL STEL) [ppm]	24 ppm
Estonia - Occupational Exposure Limits	
OEL TWA	50.1 mg/m ³
OEL TWA [ppm]	10 ppm
OEL chemical category	Skin notation
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA) [1]	35 mg/m ³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
AGW (OEL TWA) [2]	6 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Slovenia - Occupational Exposure Limits	
OEL TWA	35 mg/m ³
OEL TWA [ppm]	6 ppm
OEL STEL	70 mg/m ³
OEL STEL [ppm]	12 ppm
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	80 mg/m ³
NGV (OEL TWA) [ppm]	15 ppm
KTV (OEL STEL)	170 mg/m ³
KTV (OEL STEL) [ppm]	30 ppm
OEL chemical category	Skin notation
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA) [1]	50 mg/m ³ (aerosol, inhalable dust, vapour)
KZGW (OEL STEL)	100 mg/m ³ (aerosol, inhalable dust, vapour)
Diphenyl oxide (101-84-8)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	7 mg/m ³
IOEL TWA [ppm]	1 ppm
IOEL STEL	14 mg/m ³
IOEL STEL [ppm]	2 ppm
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	7 mg/m ³
MAK (OEL TWA) [ppm]	1 ppm
MAK (OEL STEL)	14 mg/m ³
MAK (OEL STEL) [ppm]	2 ppm

Chanel No 5 Type #EU35658F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Diphenyl oxide (101-84-8)	
Belgium - Occupational Exposure Limits	
OEL TWA	7 mg/m ³ (vapor)
OEL TWA [ppm]	1 ppm (vapor)
OEL STEL	14 mg/m ³ (vapor)
OEL STEL [ppm]	2 ppm (vapor)
Bulgaria - Occupational Exposure Limits	
OEL TWA	7 mg/m ³
OEL TWA [ppm]	1 ppm
OEL STEL	14 mg/m ³
OEL STEL [ppm]	2 ppm
Croatia - Occupational Exposure Limits	
GVI (OEL TWA) [1]	7 mg/m ³
GVI (OEL TWA) [2]	1 ppm
KGVI (OEL STEL)	14 mg/m ³
KGVI (OEL STEL) [ppm]	2 ppm
Cyprus - Occupational Exposure Limits	
OEL TWA	7 mg/m ³
OEL TWA [ppm]	1 ppm
OEL STEL	14 mg/m ³
OEL STEL [ppm]	2 ppm
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	5 mg/m ³
Denmark - Occupational Exposure Limits	
OEL TWA [1]	7 mg/m ³
OEL TWA [2]	1 ppm
Estonia - Occupational Exposure Limits	
OEL TWA	7 mg/m ³
OEL TWA [ppm]	1 ppm
OEL STEL	14 mg/m ³
OEL STEL [ppm]	2 ppm
Finland - Occupational Exposure Limits	
HTP (OEL TWA) [1]	7 mg/m ³
HTP (OEL TWA) [2]	1 ppm
HTP (OEL STEL)	14 mg/m ³
HTP (OEL STEL) [ppm]	2 ppm
France - Occupational Exposure Limits	
VME (OEL TWA)	7 mg/m ³
VME (OEL TWA) [ppm]	1 ppm
OEL chemical category	Risk of cutaneous absorption

Chanel No 5 Type #EU35658F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Diphenyl oxide (101-84-8)	
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA) [1]	7.1 mg/m ³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed-vapor)
AGW (OEL TWA) [2]	1 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed-vapor)
Gibraltar - Occupational Exposure Limits	
OEL TWA	7 mg/m ³
OEL TWA [ppm]	1 ppm
OEL STEL	14 mg/m ³
OEL STEL [ppm]	200 ppm
Greece - Occupational Exposure Limits	
OEL TWA	7 mg/m ³
OEL TWA [ppm]	1 ppm
OEL STEL	14 mg/m ³
OEL STEL [ppm]	2 ppm
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	7 mg/m ³
CK (OEL STEL)	14 mg/m ³
Ireland - Occupational Exposure Limits	
OEL TWA [1]	7 mg/m ³ (vapour)
OEL TWA [2]	1 ppm (vapour)
OEL STEL	14 mg/m ³ (vapour)
OEL STEL [ppm]	2 ppm (vapour)
Italy - Occupational Exposure Limits	
OEL TWA	7 mg/m ³
OEL TWA [ppm]	1 ppm
Latvia - Occupational Exposure Limits	
OEL TWA	7 mg/m ³
OEL TWA [ppm]	1 ppm
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	7 mg/m ³
IPRV (OEL TWA) [ppm]	1 ppm
TPRV (OEL STEL)	14 mg/m ³
TPRV (OEL STEL) [ppm]	2 ppm
Luxembourg - Occupational Exposure Limits	
OEL TWA	7 mg/m ³
OEL TWA [ppm]	1 ppm
OEL STEL	14 mg/m ³
OEL STEL [ppm]	2 ppm

Chanel No 5 Type #EU35658F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Diphenyl oxide (101-84-8)	
Malta - Occupational Exposure Limits	
OEL TWA	7 mg/m ³
OEL TWA [ppm]	1 ppm
OEL STEL	14 mg/m ³
OEL STEL [ppm]	2 ppm
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	7 mg/m ³
TGG-15min (OEL STEL)	14 mg/m ³
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	7 mg/m ³
NDSch (OEL STEL)	14 mg/m ³
Portugal - Occupational Exposure Limits	
OEL TWA	7 mg/m ³
OEL TWA [ppm]	1 ppm (vapor)
OEL STEL	14 mg/m ³ (indicative limit value)
OEL STEL [ppm]	2 ppm (indicative limit value-vapor)
Romania - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
OEL TWA [ppm]	0.7 ppm
OEL STEL	10 mg/m ³
OEL STEL [ppm]	1.4 ppm
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA) [1]	7 mg/m ³
NPHV (OEL TWA) [2]	1 ppm
NPHV (OEL C)	7.1 mg/m ³
Slovenia - Occupational Exposure Limits	
OEL TWA	7 mg/m ³
OEL TWA [ppm]	1 ppm
OEL STEL	14 mg/m ³
OEL STEL [ppm]	2 ppm
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA) [1]	7.1 mg/m ³ (vapor)
VLA-ED (OEL TWA) [2]	1 ppm (vapor)
VLA-EC (OEL STEL)	14.2 mg/m ³ (vapor)
VLA-EC (OEL STEL) [ppm]	2 ppm (vapor)
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	7 mg/m ³
NGV (OEL TWA) [ppm]	1 ppm
KTV (OEL STEL)	14 mg/m ³

Chanel No 5 Type #EU35658F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Diphenyl oxide (101-84-8)	
KTV (OEL STEL) [ppm]	2 ppm
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	7 mg/m ³
WEL TWA (OEL TWA) [2]	1 ppm
WEL STEL (OEL STEL)	14 mg/m ³
WEL STEL (OEL STEL) [ppm]	2 ppm
Norway - Occupational Exposure Limits	
Grønseverdi (OEL TWA) [1]	7 mg/m ³
Grønseverdi (OEL TWA) [2]	1 ppm
Korttidsverdi (OEL STEL)	14 mg/m ³ (value from the regulation)
Korttidsverdi (OEL STEL) [ppm]	2 ppm (value from the regulation)
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA) [1]	7 mg/m ³ (aerosol, vapour)
MAK (OEL TWA) [2]	1 ppm (aerosol, vapour)
KZGW (OEL STEL)	14 mg/m ³ (aerosol, vapour)
KZGW (OEL STEL) [ppm]	2 ppm (aerosol, vapour)
OEL chemical category	Category 2 developmental toxin, Category 2 reproductive toxin
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	1 ppm (vapor)
ACGIH OEL STEL [ppm]	2 ppm (vapor fraction)
Benzyl alcohol (100-51-6)	
Bulgaria - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	40 mg/m ³
Finland - Occupational Exposure Limits	
HTP (OEL TWA) [1]	45 mg/m ³
HTP (OEL TWA) [2]	10 ppm
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA) [1]	22 mg/m ³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
AGW (OEL TWA) [2]	5 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Chemical category	Skin notation
Latvia - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	5 mg/m ³
OEL chemical category	Skin notation

Chanel No 5 Type #EU35658F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Benzyl alcohol (100-51-6)	
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	240 mg/m ³
Slovenia - Occupational Exposure Limits	
OEL TWA	22 mg/m ³
OEL TWA [ppm]	5 ppm
OEL STEL	44 mg/m ³
OEL STEL [ppm]	10 ppm
OEL chemical category	Potential for cutaneous absorption
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA) [1]	22 mg/m ³ (aerosol, vapour)
MAK (OEL TWA) [2]	5 ppm (aerosol, vapour)
OEL chemical category	Skin notation
Benzaldehyde (100-52-7)	
Bulgaria - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Finland - Occupational Exposure Limits	
HTP (OEL TWA) [1]	4.4 mg/m ³
HTP (OEL TWA) [2]	1 ppm
HTP (OEL C)	17.4 mg/m ³
HTP (OEL C) [ppm]	4 ppm
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	5 mg/m ³
CK (OEL STEL)	10 mg/m ³
Latvia - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	5 mg/m ³
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	10 mg/m ³
NDSch (OEL STEL)	40 mg/m ³
Isoamyl acetate (123-92-2)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	270 mg/m ³
IOEL TWA [ppm]	50 ppm
IOEL STEL	540 mg/m ³
IOEL STEL [ppm]	100 ppm
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	270 mg/m ³ (Pentyl acetate (all isomers))

Chanel No 5 Type #EU35658F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Isoamyl acetate (123-92-2)	
MAK (OEL TWA) [ppm]	50 ppm (Pentyl acetate (all isomers))
MAK (OEL STEL)	540 mg/m ³ (Pentylacetate)
MAK (OEL STEL) [ppm]	100 ppm (Pentylacetate)
Belgium - Occupational Exposure Limits	
OEL TWA	270 mg/m ³
OEL TWA [ppm]	50 ppm
OEL STEL	540 mg/m ³
OEL STEL [ppm]	100 ppm
Bulgaria - Occupational Exposure Limits	
OEL TWA	270 mg/m ³
OEL TWA [ppm]	50 ppm
OEL STEL	540 mg/m ³
OEL STEL [ppm]	100 ppm
Croatia - Occupational Exposure Limits	
GVI (OEL TWA) [1]	270 mg/m ³
GVI (OEL TWA) [2]	50 ppm
KGVI (OEL STEL)	540 mg/m ³
KGVI (OEL STEL) [ppm]	100 ppm
Cyprus - Occupational Exposure Limits	
OEL TWA	270 mg/m ³
OEL TWA [ppm]	50 ppm
OEL STEL	540 mg/m ³
OEL STEL [ppm]	100 ppm
Denmark - Occupational Exposure Limits	
OEL TWA [1]	271 mg/m ³ (Amyl acetate, all isomers)
OEL TWA [2]	50 ppm (Amyl acetate, all isomers)
Estonia - Occupational Exposure Limits	
OEL TWA	270 mg/m ³
OEL TWA [ppm]	50 ppm
OEL STEL	540 mg/m ³
OEL STEL [ppm]	100 ppm
Finland - Occupational Exposure Limits	
HTP (OEL TWA) [1]	270 mg/m ³ (Pentyl acetate)
HTP (OEL TWA) [2]	50 ppm (Pentyl acetate)
HTP (OEL STEL)	540 mg/m ³
HTP (OEL STEL) [ppm]	100 ppm
France - Occupational Exposure Limits	
VME (OEL TWA)	270 mg/m ³ (restrictive limit)
VME (OEL TWA) [ppm]	50 ppm (restrictive limit)

Chanel No 5 Type #EU35658F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Isoamyl acetate (123-92-2)	
VLE (OEL C/STEL)	540 mg/m ³ (restrictive limit)
VLE (OEL C/STEL) [ppm]	100 ppm (restrictive limit)
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA) [1]	270 mg/m ³
AGW (OEL TWA) [2]	50 ppm
Gibraltar - Occupational Exposure Limits	
OEL TWA	270 mg/m ³
OEL TWA [ppm]	50 ppm
OEL STEL	540 mg/m ³
OEL STEL [ppm]	100 ppm
Greece - Occupational Exposure Limits	
OEL TWA	530 mg/m ³
OEL TWA [ppm]	100 ppm
OEL STEL	800 mg/m ³
OEL STEL [ppm]	150 ppm
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	270 mg/m ³
CK (OEL STEL)	540 mg/m ³
Ireland - Occupational Exposure Limits	
OEL TWA [1]	260 mg/m ³
OEL TWA [2]	50 ppm
OEL STEL	520 mg/m ³
OEL STEL [ppm]	100 ppm
Italy - Occupational Exposure Limits	
OEL TWA	270 mg/m ³
OEL TWA [ppm]	50 ppm
OEL STEL	540 mg/m ³
OEL STEL [ppm]	100 ppm
Latvia - Occupational Exposure Limits	
OEL TWA	270 mg/m ³
OEL TWA [ppm]	50 ppm
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	270 mg/m ³
IPRV (OEL TWA) [ppm]	50 ppm
TPRV (OEL STEL)	540 mg/m ³
TPRV (OEL STEL) [ppm]	100 ppm
Luxembourg - Occupational Exposure Limits	
OEL TWA	270 mg/m ³
OEL TWA [ppm]	50 ppm

Chanel No 5 Type #EU35658F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Isoamyl acetate (123-92-2)	
OEL STEL	540 mg/m ³
OEL STEL [ppm]	100 ppm
Malta - Occupational Exposure Limits	
OEL TWA	270 mg/m ³
OEL TWA [ppm]	50 ppm
OEL STEL	540 mg/m ³
OEL STEL [ppm]	100 ppm
Netherlands - Occupational Exposure Limits	
TGG-15min (OEL STEL)	530 mg/m ³
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	250 mg/m ³
NDSch (OEL STEL)	500 mg/m ³
Portugal - Occupational Exposure Limits	
OEL TWA	270 mg/m ³ (indicative limit value)
OEL TWA [ppm]	50 ppm (indicative limit value)
OEL STEL	540 mg/m ³ (indicative limit value)
OEL STEL [ppm]	100 ppm (indicative limit value, regulated under Pentyl acetate, all isomers)
Romania - Occupational Exposure Limits	
OEL TWA	270 mg/m ³
OEL TWA [ppm]	50 ppm
OEL STEL	540 mg/m ³
OEL STEL [ppm]	100 ppm
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA) [1]	270 mg/m ³
NPHV (OEL TWA) [2]	50 ppm
NPHV (OEL C)	540 mg/m ³
Slovenia - Occupational Exposure Limits	
OEL TWA	270 mg/m ³
OEL TWA [ppm]	50 ppm
OEL STEL	540 mg/m ³
OEL STEL [ppm]	100 ppm
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA) [1]	270 mg/m ³ (indicative limit value)
VLA-ED (OEL TWA) [2]	50 ppm (indicative limit value)
VLA-EC (OEL STEL)	540 mg/m ³
VLA-EC (OEL STEL) [ppm]	100 ppm
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	270 mg/m ³ (Pentyl acetates)
NGV (OEL TWA) [ppm]	50 ppm (Pentyl acetates)

Chanel No 5 Type #EU35658F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Isoamyl acetate (123-92-2)	
KTV (OEL STEL)	540 mg/m ³ (Pentyl acetates)
KTV (OEL STEL) [ppm]	100 ppm (Pentyl acetates)
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA) [1]	260 mg/m ³
Grenseverdi (OEL TWA) [2]	50 ppm
Korttidsverdi (OEL STEL)	325 mg/m ³ (value calculated)
Korttidsverdi (OEL STEL) [ppm]	75 ppm (value calculated)
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	50 ppm (Pentyl acetate, all isomers)
ACGIH OEL STEL [ppm]	100 ppm (Pentyl acetate, all isomers)

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

Chanel No 5 Type #EU35658F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: light yellow. amber.
Odour	: characteristic. characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not available
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: > 93 °C (closed cup) ASTM D7094
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: ≈ 1.11
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

Chanel No 5 Type #EU35658F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Harmful if swallowed.
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Chanel No 5 Type #EU35658F

ATE CLP (oral)	808.407 mg/kg bodyweight
----------------	--------------------------

Benzyl benzoate (120-51-4)

LD50 oral rat	500 mg/kg
LD50 oral	1500 mg/kg bodyweight
LD50 dermal rabbit	4000 mg/kg
LD50 dermal	4000 mg/kg bodyweight

Amyl cinnamic aldehyde (122-40-7)

LD50 oral rat	3730 mg/kg
LD50 dermal rabbit	> 2000 mg/kg

Benzyl acetate (140-11-4)

LD50 oral rat	2490 mg/kg
LD50 oral	2490 mg/kg bodyweight
LD50 dermal rabbit	> 5000 mg/kg

Methyl ionone (mixture of isomers) (1335-46-2)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LD50 dermal	2900 mg/kg bodyweight

Linalool (78-70-6)

LD50 oral	2790 mg/kg bodyweight
-----------	-----------------------

Musk ketone (81-14-1)

LD50 oral rat	10 g/kg
LD50 dermal rabbit	> 10 g/kg
LC50 Inhalation - Rat	> 2.99 mg/l/4h

Heliotropine (120-57-0)

LD50 oral rat	2700 mg/kg
LD50 oral	2700 mg/kg bodyweight
LD50 dermal rat	> 5000 mg/kg

COUMARIN (91-64-5)

LD50 oral rat	> 5000 mg/kg
LD50 oral	500 mg/kg bodyweight

Chanel No 5 Type #EU35658F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

COUMARIN (91-64-5)	
LD50 dermal rat	293 mg/kg
Hexamethylindanopyran (1222-05-5)	
LD50 oral rat	> 3250 mg/kg
LD50 dermal rabbit	> 3250 mg/kg
Hydroxy (107-75-5)	
LD50 oral rat	> 5 g/kg
LD50 dermal rabbit	> 2000 mg/kg
Citronellol Pure (106-22-9)	
LD50 oral rat	3450 mg/kg
LD50 oral	3450 mg/kg bodyweight
LD50 dermal rabbit	2650 mg/kg
LD50 dermal	2650 mg/kg bodyweight
alpha-Ionone (127-41-3)	
LD50 oral	4590 mg/kg bodyweight
Vanillin (121-33-5)	
LD50 dermal rabbit	> 5010 mg/kg
LD50 dermal	2600 mg/kg bodyweight
Linalyl acetate (115-95-7)	
LD50 oral rat	14550 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
Amyl salicylate (2050-08-0)	
LD50 oral rat	4100 mg/kg
LD50 oral	2000 mg/kg bodyweight
LD50 dermal rabbit	> 5000 mg/kg
Geraniol (106-24-1)	
LD50 oral rat	3600 mg/kg
LD50 oral	3600 mg/kg bodyweight
LD50 dermal rabbit	> 5 g/kg
Nerol (106-25-2)	
LD50 oral rat	4500 mg/kg
LD50 oral	4500 mg/kg bodyweight
LD50 dermal rabbit	> 5 g/kg
Citral (5392-40-5)	
LD50 oral rat	4960 mg/kg
LD50 dermal rabbit	2250 mg/kg
LD50 dermal	2250 mg/kg bodyweight

Chanel No 5 Type #EU35658F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

d-Limonene (5989-27-5)	
LD50 oral rat	4400 mg/kg
LD50 dermal rabbit	> 5 g/kg
Eugenol (97-53-0)	
LD50 oral rat	1930 mg/kg
LD50 oral	2500 mg/kg bodyweight
Cinnamic alcohol (104-54-1)	
LD50 oral	2000 mg/kg bodyweight
LD50 dermal rabbit	> 5000 mg/kg
Carbitol (111-90-0)	
LD50 oral rat	10502 mg/kg
LD50 dermal rabbit	9143 mg/kg
LC50 Inhalation - Rat	> 5240 mg/m ³ (Exposure time: 4 h)
Timberol (70788-30-6)	
LD50 dermal rabbit	> 2000 mg/kg
Camphene (79-92-5)	
LD50 oral rat	5600 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
para-Cresyl methyl ether (104-93-8)	
LD50 oral rat	1920 mg/kg
LD50 oral	1900 mg/kg bodyweight
LD50 dermal rabbit	> 5 g/kg
LC50 Inhalation - Rat	> 6.1 mg/l/4h
Diphenyl oxide (101-84-8)	
LD50 oral rat	2450 mg/kg
LD50 oral	2830 mg/kg bodyweight
LD50 dermal rabbit	> 7940 mg/kg
LC50 Inhalation - Rat (Dust/Mist)	1.5 mg/l/4h
Benzyl alcohol (100-51-6)	
LD50 oral rat	1230 mg/kg
LD50 oral	1620 mg/kg bodyweight
LD50 dermal	2500 mg/kg bodyweight
Methyl salicylate (119-36-8)	
LD50 oral rat	887 mg/kg
LD50 oral	890 mg/kg bodyweight
LD50 dermal rabbit	> 5000 mg/kg
Benzaldehyde (100-52-7)	
LD50 oral rat	1292 mg/kg

Chanel No 5 Type #EU35658F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Benzaldehyde (100-52-7)	
LD50 dermal rabbit	> 1250 mg/kg
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.
Benzyl acetate (140-11-4)	
IARC group	3 - Not classifiable
COUMARIN (91-64-5)	
IARC group	3 - Not classifiable
d-Limonene (5989-27-5)	
IARC group	3 - Not classifiable
Eugenol (97-53-0)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Benzyl benzoate (120-51-4)	
Viscosity, kinematic	7.456 mm ² /s
Heliotropine (120-57-0)	
Viscosity, kinematic	Not applicable

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.

Benzyl benzoate (120-51-4)	
LC50 - Fish [1]	2.32 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static])
NOEC (chronic)	0.168 mg/l
Methyl ionone (mixture of isomers) (1335-46-2)	
LC50 - Fish [1]	2.3 mg/l (Exposure time: 96 h - Species: Danio rerio [static])
Linalool (78-70-6)	
EC50 96h - Algae [1]	88.3 mg/l (Species: Desmodemus subspicatus)
Heliotropine (120-57-0)	
LC50 - Fish [1]	2.5 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [static])

Chanel No 5 Type #EU35658F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hexamethylindanopyran (1222-05-5)	
LC50 - Fish [1]	0.452 mg/l Wolf, 1996d-27682
LC50 - Other aquatic organisms [1]	> 0.14 mg/l REACH DOSSIER Pimephales promelas
EC50 - Crustacea [2]	260 µg/l REACH Dossier
EC50 - Other aquatic organisms [1]	0.131 mg/l REACH Dossier
Vanillin (121-33-5)	
LC50 - Fish [1]	53 – 61.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 - Fish [2]	88 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
NOEC (acute)	10000 mg/kg (Exposure time: 42 Days - Species: Eisenia foetida [soil dry weight])
Linalyl acetate (115-95-7)	
LC50 - Fish [1]	11 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [flow-through])
Geraniol (106-24-1)	
LC50 - Fish [1]	22 mg/l (Exposure time: 96 h - Species: Danio rerio [static])
Nerol (106-25-2)	
LC50 - Fish [1]	20.3 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static])
Citral (5392-40-5)	
EC50 - Crustacea [1]	7 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	16 mg/l (Species: Desmodesmus subspicatus)
EC50 96h - Algae [1]	19 mg/l (Species: Desmodesmus subspicatus)
d-Limonene (5989-27-5)	
LC50 - Fish [1]	0.619 – 0.796 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 - Fish [2]	35 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
Eugenol (97-53-0)	
LC50 - Fish [1]	13 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static])
Carbitol (111-90-0)	
LC50 - Fish [1]	10000 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
LC50 - Fish [2]	19100 – 23900 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [flow-through])
EC50 - Crustacea [1]	3940 – 4670 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Camphene (79-92-5)	
LC50 - Fish [1]	0.72 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [flow-through])
LC50 - Fish [2]	150 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])
EC50 - Crustacea [1]	22 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	> 1000 mg/l (Species: Desmodesmus subspicatus)
para-Cresyl methyl ether (104-93-8)	
EC50 - Crustacea [1]	44.2 mg/l (Exposure time: 48 h - Species: Daphnia magna Straus)
EC50 72h - Algae [1]	320 mg/l (Species: Desmodesmus subspicatus)
EC50 96h - Algae [1]	390 mg/l (Species: Desmodesmus subspicatus)

Chanel No 5 Type #EU35658F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Benzyl alcohol (100-51-6)	
LC50 - Fish [1]	460 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
LC50 - Fish [2]	10 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 - Crustacea [1]	23 mg/l (Exposure time: 48 h - Species: water flea)
Benzaldehyde (100-52-7)	
LC50 - Fish [1]	10.6 – 11.8 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
LC50 - Fish [2]	12.69 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
12.2. Persistence and degradability	
Benzyl benzoate (120-51-4)	
Persistence and degradability	May cause long-term adverse effects in the environment.
Cedarwood oil, Texas (68990-83-0)	
Persistence and degradability	Not established.
12.3. Bioaccumulative potential	
Benzyl benzoate (120-51-4)	
Partition coefficient n-octanol/water (Log Pow)	3.97 (at 25 °C)
Bioaccumulative potential	Not established.
Amyl cinnamic aldehyde (122-40-7)	
Partition coefficient n-octanol/water (Log Pow)	2.498 (at 25 °C (at pH 6.2))
Benzyl acetate (140-11-4)	
Partition coefficient n-octanol/water (Log Pow)	1.96 (at 25 °C (at pH 7))
Methyl ionone (mixture of isomers) (1335-46-2)	
Partition coefficient n-octanol/water (Log Pow)	(>4.5 - <5 - at 23 °C (at pH 6.2))
Musk ketone (81-14-1)	
Partition coefficient n-octanol/water (Log Pow)	4.24 (at 25 °C)
Heliotropine (120-57-0)	
Partition coefficient n-octanol/water (Log Pow)	1.2 (at 35 °C)
Hexamethylindanopyran (1222-05-5)	
BCF - Fish [1]	(1618 dimensionless (whole body w.w.))
Partition coefficient n-octanol/water (Log Pow)	5.3 (at 25 °C (at pH 7))
Hydroxy (107-75-5)	
Partition coefficient n-octanol/water (Log Pow)	1.68 (at 25 °C)
Citronellol Pure (106-22-9)	
Partition coefficient n-octanol/water (Log Pow)	3.41 (at 25 °C)
alpha-Ionone (127-41-3)	
Partition coefficient n-octanol/water (Log Pow)	3.896 (at 25 °C (at pH 7.2))

Chanel No 5 Type #EU35658F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Vanillin (121-33-5)	
Partition coefficient n-octanol/water (Log Pow)	1.23 (at 22 °C)
Linalyl acetate (115-95-7)	
Partition coefficient n-octanol/water (Log Pow)	3.9 (at 25 °C)
Amyl salicylate (2050-08-0)	
BCF - Fish [1]	(1170 dimensionless (whole body w.w.))
Partition coefficient n-octanol/water (Log Pow)	4.5 (at 30 °C)
Geraniol (106-24-1)	
Partition coefficient n-octanol/water (Log Pow)	2.6 (at 25 °C)
Nerol (106-25-2)	
Partition coefficient n-octanol/water (Log Pow)	2.76 (at 30 °C (at pH 6.5))
Citral (5392-40-5)	
Partition coefficient n-octanol/water (Log Pow)	2.76 (at 25 °C)
d-Limonene (5989-27-5)	
Partition coefficient n-octanol/water (Log Pow)	4.38 (at 37 °C (at pH 7.2))
Eugenol (97-53-0)	
Partition coefficient n-octanol/water (Log Pow)	1.83 (at 30 °C (at pH 5.5))
Cinnamic alcohol (104-54-1)	
Partition coefficient n-octanol/water (Log Pow)	1.636 (at 27 °C (at pH 3.52))
Carbitol (111-90-0)	
Partition coefficient n-octanol/water (Log Pow)	-0.8
Timberol (70788-30-6)	
Partition coefficient n-octanol/water (Log Pow)	5.79 (at 25 °C (at pH 5.85))
Camphene (79-92-5)	
Partition coefficient n-octanol/water (Log Pow)	4.22 (at 37 °C (at pH 7.2))
para-Cresyl methyl ether (104-93-8)	
Partition coefficient n-octanol/water (Log Pow)	2.8 (at 35 °C (at pH 7))
Cedarwood oil, Texas (68990-83-0)	
Bioaccumulative potential	Not established.
Diphenyl oxide (101-84-8)	
BCF - Fish [1]	(470 dimensionless)
Partition coefficient n-octanol/water (Log Pow)	4.21 (at 25 °C)
Benzyl alcohol (100-51-6)	
Partition coefficient n-octanol/water (Log Pow)	1.05
Methyl salicylate (119-36-8)	
Partition coefficient n-octanol/water (Log Pow)	2.55

Chanel No 5 Type #EU35658F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Benzaldehyde (100-52-7)

BCF - Fish [1]	(no significant bioaccumulation)
Partition coefficient n-octanol/water (Log Pow)	1.4 (at 25 °C)

Isoamyl acetate (123-92-2)

Partition coefficient n-octanol/water (Log Pow)	2.7 (at 35 °C)
---	----------------

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
HP Code	: HP3 - "Flammable:" <ul style="list-style-type: none">– flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;– flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;– flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;– flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa;– water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;– other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.
	HP6 - "Acute Toxicity:" waste which can cause acute toxic effects following oral or dermal administration, or inhalation exposure.
	HP7 - "Carcinogenic:" waste which induces cancer or increases its incidence
	HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information






In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 3082	UN 3082	UN 3082	UN 3082	UN 3082
14.2. UN proper shipping name				
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Musk Ketone)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Musk Ketone)	Environmentally hazardous substance, liquid, n.o.s. (Musk Ketone)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Musk Ketone)	(Musk Ketone)

Chanel No 5 Type #EU35658F


Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
Transport document description				
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Musk Ketone), 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Musk Ketone), 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (Musk Ketone), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Musk Ketone), 9, III	UN 3082 (Musk Ketone)
14.3. Transport hazard class(es)				
9	9	9	9	Not applicable
				
14.4. Packing group				
III	III	III	III	Not applicable
14.5. Environmental hazards				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: M6
Special provisions (ADR)	: 274, 335, 375, 601
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBV
Vehicle for tank carriage	: AT
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV13
Hazard identification number (Kemler No.)	: 90
Orange plates	: 
Tunnel restriction code (ADR)	: -
EAC code	: •3Z

Transport by sea

Special provisions (IMDG)	: 274, 335, 969
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: LP01, P001
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03

Chanel No 5 Type #EU35658F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP2, TP29
EmS-No. (Fire)	: F-A
EmS-No. (Spillage)	: S-F
Stowage category (IMDG)	: A

Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y964
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 964
PCA max net quantity (IATA)	: 450L
CAO packing instructions (IATA)	: 964
CAO max net quantity (IATA)	: 450L
Special provisions (IATA)	: A97, A158, A197
ERG code (IATA)	: 9L

Inland waterway transport

Classification code (ADN)	: M6
Special provisions (ADN)	: 274, 335, 375, 601
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1
Equipment required (ADN)	: PP
Number of blue cones/lights (ADN)	: 0

Rail transport

No data available

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(a)	d-Limonene ; Isoamyl acetate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	Chanel No 5 Type #EU35658F ; Benzyl benzoate ; Amyl cinnamic aldehyde ; Methyl ionone (mixture of isomers) ; Linalool ; Musk ketone ; Hydroxy ; Citronellol Pure ; Linalyl acetate ; Amyl salicylate ; Geraniol ; Nerol ; Citral ; d-Limonene ; Eugenol ; Timberol ; para-Cresyl methyl ether ; Cedarwood oil, Texas ; Benzyl alcohol ; Methyl salicylate ; Benzaldehyde	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10

Chanel No 5 Type #EU35658F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(c)	Chanel No 5 Type #EU35658F ; Benzyl benzoate ; Amyl cinnamic aldehyde ; Benzyl acetate ; Methyl ionone (mixture of isomers) ; Musk ketone ; Hexamethylindanopyran ; alpha-Ionone ; Amyl salicylate ; d-Limonene ; Cedarwood oil, Texas ; Methyl salicylate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
40.	d-Limonene ; Camphene ; Isoamyl acetate	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category	Threshold	Annex
Piperonal		120-57-0	2932 93 00	Category 1		Annex I

15.1.2. National regulations

France

Occupational diseases	
Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG).
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG).

Chanel No 5 Type #EU35658F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).
Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

ABM category : A(1) - highly toxic for aquatic organisms, may have longterm hazardous effects in aquatic environment
SZW-lijst van kankerverwekkende stoffen : Timberol, Cedarwood oil, Texas are listed
SZW-lijst van mutagene stoffen : Timberol is listed
SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling : Methyl salicylate is listed

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

Switzerland

Storage class (LK) : LK 6.1 - Toxic materials

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Full text of H- and EUH-statements:	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Flam. Sol. 2	Flammable solids, Category 2
H226	Flammable liquid and vapour.
H228	Flammable solid.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.

Chanel No 5 Type #EU35658F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H351	Suspected of causing cancer.
H361	Suspected of damaging fertility or the unborn child.
H361d	Suspected of damaging the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.